

Coatings containing silicon on advanced titanium alloys.

Katarzyna Leszczynska

AGH University of Science and Technology, Faculty of Materials Science and Ceramics, Al.
A. Mickiewicza 30, 30-059 Krakow, Poland

leszczynska.katarzyn@gmail.com, contact phone: +48 126174787

Abstract

Advanced titanium alloys based on γ -TiAl and α_2 -Ti₃Al draw attention as lightweight structural materials in aircraft and automotive industry. However, their insufficient resistance to hot corrosion calls for development of appropriate protection systems. It is expected that silicon-containing coatings will provide a satisfactory protection, since SiO₂ is known for thermodynamic stability in hot-salt environments.

In this work, a silicon-containing coating was deposited on a Ti-46Al-8Ta (at%) alloy in a two-step process, comprising physical and chemical vapour deposition. The as-received coating was adherent and its thickness was about 40 μ m. To evaluate protective properties of the coating, the samples were contaminated with a mixture of NaCl and Na₂SO₄ in a mass ratio of 1:3 and oxidized in thermal cycling conditions in air at 800°C. Reaction progress was followed by thermogravimetric measurements. Significant improvement in hot corrosion resistance was noted for the coated samples compared with the uncoated reference. The post-exposure examination included scanning electron microscopy (SEM) with energy dispersive X-ray analysis (EDS/EDAX) and X-ray diffraction (XRD).

Acknowledgements

The author gratefully acknowledges financial support from the statutory funds of the Department of Inorganic Chemistry at the Faculty of Materials Science and Ceramics, AGH UST, Krakow, Poland (2012).